



Au OB2 CAN Cable with a DB9 Female Connector, OB2-II Receptacle Housing and Power Jacket

(Part#: CBL-OB2-CAN-02)

Rev. A
May 2023

J1939/J1708 cable (Part#: CBL-OB2-CAN-02) equipped with a DB9 female connector, an OB2-II Wire-to-Wire Receptacle Housing and a power jacket.



The DB9 female connector can be connected with Au Group Electronics OB2 CAN simulators. It will supply power, ground, CAN-H, CAN-L, to Au Group Electronics developed OB2 CAN devices.

The other end of the cable includes an OB2-II Wire-to-Wire Receptacle Housing (4.00mm Pitch, Flange Mount) and a power supply jacket (2.1 mm positive center). The OB2-II Wire-to-Wire Receptacle Housing on CBL-OB2-CAN-02 can mate with the OB2-II male housing on OB2 diagnostic tool.

This cable are frequently used together with Au OB2 CAN simulator. It may also be used for third-party devices designed by J1979 and J1979-2 specification.

Specification:

Maximum cable length: 10 inches

OB2-II connector: 4.00mm Pitch OB2-II Wire-to-Wire Receptacle Housing

Power Jacket: 2.1mm DC Power Socket, positive center

Weight: 65 gram

Maximum current: 4A (continuous) Maximum voltage: 300V DC

Pin out and wire diagram CBL-OB2-CAN-02:

